

SLS - CABINETS WIDTH 1200 MM AS PER TRGS 526 / DGUV

For storage of acids and alkalis

- Body made from HPL-coated sheets particularly impact, scratch and abrasion proof
- ◆ Color RAL 7035 light grey
- Inner body / inner fittings completely made from corrosion-proof components
- Doors with separate cylinder locks
- Marking according to ASR A1.3
- ◆ Leveling feets for installing cabinet horizontally
- With central horizontal and vertical divisions for storage of acids and alkalis in 4 separate compartments
- ♦ Model SLS 1200 GL with acrylic glass doors
- ◆ Air supply by ventilation grille in the back wall
- ◆ DN 80 ventilation connection for exhaust air extraction on cabinet roof



SLS 1200/12, Article no. B80-3016-D

Extraction fans please see page 136!

With inner fittings:

- Pull-out shelves (to full extent) with end stop
 - · Max. load 20 kg per shelf
 - Front edge of shelves in attractive solid wood design
 - PE sump tray (sump capacity 20 liters) on shelf secured against slipping - easy to remove





Model	SLS 1200/8	SLS 1200/12	SLS 1200 GL/8	SLS 1200 GL/12
External dimensions				
W x D x H (mm)	1200 x 600 x 1935	1200 x 600 x 1935	1200 x 600 x 1935	1200 x 600 x 1935
Pull-out shelves	4 x 2	4 x 3	4 x 2	4 x 3
Usable inner shelf height (mm)	8 x 420	8 x 275 / 4 x 248	8 x 420	8 x 275 / 4 x 248
Doors	4	4	4 (acrylic glass doors)	4 (acrylic glass doors)
Weight (kg)	220	232	220	232
Article no., outer body:				
RAL 7035 - light grey	B80-3017-D	B80-3016-D	B80-3022-D	B80-3023-D

Accessory	Article no.
Pull-out shelf	R80-2870-∆

6 SLS 1200/12, Article no. B80-3016-D (page 87)



3 SLS 1200/6-SF6, Article no. B80-3025-D (page 88)









store **LAB**

SLS 1200 GL/6-SF6,

Article no. B80-3027-D



SLS - CABINETS WIDTH 1200 MM AS PER TRGS 526 / DGUV

fans

For storage of acids and alkalis

- Body made from HPL-coated sheets particularly impact, scratch and abrasion proof
- Color RAL 7035 light grey
- ♦ Inner body / inner fittings completely made from corrosion-proof components
- ◆ Doors with separate cylinder locks, 6 drawers in lower part
- Marking according to ASR A1.3
- Leveling feets for installing cabinet horizontally
- With central horizontal and vertical divisions for storage of acids and alkalis in 4 separate compartments
- ◆ Model SLS 1200 GL with acrylic glass doors
- Supply air by ventilation grille in the back wall
- ◆ DN 80 ventilation connection for exhaust air extraction on cabinet roof

With inner fittings:

- Pull-out shelves (to full extent) with end stop
 - Max. load 20 kg per shelf
 - Front edge of shelves in attractive solid wood design
 - PE sump tray (sump capacity 20 liters) on shelf secured against slipping - easy to remove
- ◆ Pull-out drawers (to full extent) with end stop
 - Max. load 20 kg per drawer
 - PE sump tray (sump capacity 20 liters) in drawer secured against slipping - easy to remove











Pull-out drawer with end stop

Model	SLS 1200/4-SF 6	SLS 1200/6-SF6	SLS 1200 GL/4-SF6	SLS 1200 GL/6-SF6
External dimensions W x D x H (mm)	1200 x 600 x 1935			
Pull-out shelves	2 x 2	2 x 3	2 x 2	2 x 3
Usable inner shelf				
height (mm)	4 x 420	4 x 275 / 2 x 248	4 x 420	4 x 275 / 2 x 248
Drawers	6	6	6	6
Usable inner drawer				
height (mm)	2 x 255 / 2 x 275 / 2 x 250	2 x 255 / 2 x 275 / 2 x 250	2 x 255 / 2 x 275 / 2 x 250	2 x 255 / 2 x 275 / 2 x 250
Doors	2	2	2 (acrylic glass doors)	2 (acrylic glass doors)
Weight (kg)	220	232	220	232
Article no., outer body:				
RAL 7035 - light grey	B80-3024-D	B80-3025-D	B80-3026-D	B80-3027-D

Article no. B80-3027-D

Accessory	Article no.
Pull-out shelf	B80-2870-A