



Explanations see practical informations on page 6 and 84!

## ROOF, SIDEWALLS AND BACK WALLS IN F90 VERSION

- ◆ For regular storage outdoors of pressurized gas cylinders in accordance with TRGS 510
- ◆ Roof and walls in fire-resistant version as per DIN 4102
- ◆ Cantilever arm compartment divider with safety chains (fold out)
- ◆ Mounted delivery
- ◆ Lockable grilled door
- ◆ With hinged or double-hinged door depending on version

**Delivered fully assembled!**



**Installation directly next to building without safety distance!**

**GFL-F90-6.08, Article no. C66-2010-A**



**GFL-F90-24.21, Article no. C66-2014-A, with optional partition wall**



**GFL-F90 with closed door (available for all types, price on request)**



**GFL-F90 in special design**

Model	GFL-F90-6.08	GFL-F90-8.11	GFL-F90-12.11	GFL-F90-16.21	GFL-F90-24.21	GFL-F90-32.21
External dimensions W x D x H (mm)	1120 x 1270 x 2310	1370 x 1270 x 2310	1370 x 1420 x 2310	2390 x 1270 x 2310	2390 x 1420 x 2310	2390 x 1620 x 2310
Internal dimensions W x D x H (mm)	800 x 920 x 2000	1050 x 920 x 2000	1050 x 1080 x 2000	2050 x 920 x 2000	2050 x 1080 x 2000	2050 x 1230 x 2000
Door version	Hinged door DIN right	Hinged door DIN right	Hinged door DIN right	Double-hinged door	Double-hinged door	Double-hinged door
Capacity, gas cylinders ø 220 mm	6	8	12	16	24	32
<b>Article no., painted, without base group</b>	<b>C66-2000-A</b>	<b>C66-2001-A</b>	<b>C66-2002-A</b>	<b>C66-2003-A</b>	<b>C66-2004-A</b>	<b>C66-2005-A</b>
<b>Article no., painted, with base group</b>	<b>C66-2010-A</b>	<b>C66-2011-A</b>	<b>C66-2012-A</b>	<b>C66-2013-A</b>	<b>C66-2014-A</b>	<b>C66-2015-A</b>

Accessories	Article no.
Ramp, galvanized	<b>C66-2020-A</b>
Partition wall depth 920 mm: GFL-F90-6.08/-8.11/-16.21	<b>C66-2021-A</b>
Partition wall depth 1080 mm: GFL-F90-12.11/-24.21	<b>C66-2022-A</b>
Partition wall depth 1230 mm: GFL-F90-32.21	<b>C66-2023-A</b>