

## TYPE 90 / 600 KL - KOMBILAB AS PER DIN EN 14470-1 (TYPE 90)

Approved for the storage of flammable liquids at the workplace as per DIN EN 14470-1 (type 90) and TRGS 510, annex 1, toxic and very toxic substances, acids and alkalis. Ideal combination for storage of various hazardous substances in a very small space.



# **1** Safety cabinet (type 90) for flammable liquids as per DIN EN 14470-1

- Whole construction tested and approved by an authorized materials testing institute as per DIN EN 14470-1 (type 90) with a fire resistance of >90 minutes
- ◆ GS-approved safety (GS-sign)
- Insulation according to DIN 4102
- Outer body made from powder-coated sheet steel, RAL 7035 light grey
- Inner body made from HPL coated sheets RAL 7035
- Stainless steel base plate Niro Rhombus
- Shelf height-adjustable at intervals of 64 mm
- DN 80 ventilation connection for exhaust air extraction on cabinet roof
- Operation complies with TRGS 510 (approved even with exhaust air connection!)
- Ground connection in accordance with TRBS 2153 (avoidance of sources of ignition)
- Markings according to DIN EN 14470-1 / TRGS 510 / ISO 3864 / ASR A1.3
- Leveling feets for installing cabinet horizontally

2

Doors with cylinder lock





Type 90 / 600 KL1, Article no. B80-2887-A

#### With inner fittings:

## **1** Safety cabinet (type 90)

- 1 x base sump tray (sump capacity 22 liters) as per WHG - Ü-sign according

#### to StawaR

- 1 x perforated base tray cover as 1st storing level
- 2 x shelf
- With automatic thermal closing mechanism if fire occurs
- Door after temperature increase to ≤50°C and
- Inlet and outlet channels after temperature increase to 70°C (±10°C)
- door hold-open device

### Poison compartment with acrylic glass door

- Dividing shelf
- or
- Fully rotating turntable

595 x 600 x 1935
2
-
1
250
B80-2888-A
B80-2889-A



Type 90 / 600 KL2, Article no. B80-2889-A